







Staufix Basic		Installation in an exposed wastewater pipe	
Illustration and dimensioned drawing	Article description	Outer diameter Ø (mm)	Article #
 <p style="margin-top: 10px;">Illustration shows 1</p> <p style="margin-top: 10px;">Installation area 650 x 300 mm</p>	<p>Twin flap backwater valve <i>Staufix Basic</i> made of polymer, Ø... with emergency closure</p> <p>1 with two polymer flaps</p> <p>2 with one polymer flap and one stainless steel rodent protection flap (version R)</p> <p>Twin flaps, self-closing, one of which can be locked by hand as an emergency closure. Inlet/outlet for connection to PVC pipe according to EN 1566-1.</p> <p>Ø 110 L: 355 H: 180+25 AxB: 205 x 155 mm Ø 125 L: 405 H: 240+40 AxB: 270 x 200 mm Ø 160 L: 450 H: 240+40 AxB: 270 x 200 mm Ø 200 L: 530 H: 278+50 AxB: 353 x 248 mm</p> <p style="font-size: 24px; font-weight: bold;">Ⓒ</p> <p>EN 13564 Type 2</p>	<p>1 With two polymer flaps</p> <p>Ø 110 Ø 125 Ø 160 Ø 200</p> <p>2 With two polymer flaps and one stainless steel rodent protection flap</p> <p>Ø 110 Ø 125 Ø 160</p>	<p>73100 73125 73150 73200</p> <p>73100R 73125R 73150R</p>
 <p style="margin-top: 10px;">Illustration shows 1</p> <p style="margin-top: 10px;">Installation area 650 x 300 mm</p>	<p>Single flap backwater valve <i>Staufix Basic</i> made of polymer, Ø... with emergency closure</p> <p>1 with one polymer flap</p> <p>2 with one stainless steel rodent protection flap (version R)</p> <p>Self-closing flap, can be locked by hand as an emergency closure. Inlet/outlet for connection to PVC pipe according to EN 1566-1.</p> <p>Ø 100 L: 355 H: 180+25 AxB: 205 x 155 mm Ø 110 L: 355 H: 180+25 AxB: 205 x 155 mm Ø 125 L: 405 H: 240+40 AxB: 270 x 200 mm Ø 160 L: 450 H: 240+40 AxB: 270 x 200 mm Ø 200 L: 530 H: 278+50 AxB: 353 x 248 mm</p> <p style="font-size: 24px; font-weight: bold;">Ⓒ</p> <p>EN 13564 Type 1</p>	<p>1 With one polymer flap</p> <p>Ø 100 Ø 110 Ø 125 Ø 160 Ø 200</p> <p>2 With one stainless steel rodent protection flap</p> <p>Ø 110 Ø 125 Ø 160</p>	<p>77100 72100 72125 72150 72200</p> <p>72100R 72125R 72150R</p>
 <p style="margin-top: 10px;">Installation area 650 x 300 mm</p>	<p>Single flap backwater valve <i>Staufix Basic</i> made of polymer, Ø... without emergency closure</p> <p><input type="checkbox"/> with one polymer flap</p> <p>Self-closing flap. Inlet/outlet for connection to PVC pipe according to EN 1566-1.</p> <p>Ø 100 L: 355 H: 170 A x B: 205 x 155 mm Ø 110 L: 355 H: 170 A x B: 205 x 155 mm Ø 125 L: 405 H: 230 A x B: 270 x 200 mm Ø 160 L: 450 H: 230 A x B: 270 x 200 mm Ø 200 L: 530 H: 278 A x B: 353 x 248 mm</p> <p style="font-size: 24px; font-weight: bold;">Ⓒ</p> <p>EN 13564 Type 0</p>	<p>Ø 100 Ø 110 Ø 125 Ø 160 Ø 200</p>	<p>76100 71100 71125 71150 71200</p>
 <p style="margin-top: 10px;">Installation area 650 x 300 mm</p>	<p>Clean out <i>Staufix Basic</i> made of polymer, Ø... upgradable to all <i>Staufix</i> model backwater valves</p> <p>Ø 110 L: 355 H: 170 AxB: 205 x 155 mm Ø 125 L: 405 H: 230 AxB: 270 x 200 mm Ø 160 L: 450 H: 230 AxB: 270 x 200 mm Ø 200 L: 530 H: 278 AxB: 353 x 248 mm</p>	<p>Ø 110 Ø 125 Ø 160 Ø 200</p>	<p>70100 70125 70150 70200</p>